

Thick Display 77

AUTOMATIC

2 gr • 3 gr



with optional
LED lights on the groups,
black matt sides and
actronic injection autosteamer

With touchpad above the groups and joystick taps,

it's the evolution of Etnica Display and so the top of the range too. Always automatic, with covered groups and display, it represents, as Etnica Display, the indivisible bond between modern and ancient, where the future is son of history and the most modern technology matches with sounds and past times.











AUTOMATIC 2 gr • 3 gr

Strumenti per l'Espresso

TECHNICAL FEATURES		AUTOMATIC	
Espresso coffee and cappuccino machine with thermosiphonic syst	em	2gr	3gr
Programmable portion control		•	•
E 61 brewing groups		•	•
Frame of pure polished and satined stainless steel AISI 304. Finishing of transparent methacrylate			•
Flanged boiler of copper, pipes of copper and pipe fittings of brass			•
Dual gauges for boiler and pump pressure control			•
Manual and automatic boiler water loading			•
Boiler tap for manual discharge		•	•
Built-in RPM motor pump with WATER cooling / Fluid-o-Tech rotary pump		•	•
Touchpad for each group with pilot lights for activated brewing buttons:			
6 volumetric metering selections programmable from the touchpad directly and 1 programming button			
1 electromechanical button for every group for brewing choose (only for 2 groups in the 3 groups version)		•	•
Indicator to inform the machine and cup-warmer are ON		•	•
LED lights on the back panel (with ON/OFF switch)			•
Electric cup-warmer (with ON/OFF switch)			•
Visual boiler water gauge		•	•
2 multidirectional stainless steel steam wands with manual control from the taps with joystick		•	•
1 multidirectional stainless steel hot water wand with manual control from the button		•	•
Alphameric display allowing			
to plan following functions:	to display fallowing data:		
Switching ON/OFF time of the machine	Functional test / Malfunctioning notice	•	•
Cup warmer working temperature	Coffee counting for single group and single metering		
Warning of softener regeneration	Temperature and working boiler		
Auto Steamer temperature	Boiler pressure		
OPTIONALS ON DEMAND			
Mixed hot water outlet		•	•
External motor pump			•
Raised groups			•
Cappuccino maker / Milk frothing wand			•

TECHNICAL DATA		2 gr	3 gr
Power	W	2500/3900	5560
Voltage	V	120 - 230 - 240 - 400 (1F-3F) / 50 - 60 Hz	230 - 240 - 400 (1F-3F) / 50 - 60 Hz
Boiler	Lt	12	17
Width	mm	740	980
Depth	mm	600	
Height	mm	560	
Net weight	Ka	65	96

Electronic injection autosteamer with adjustable control of speed and of pump capacity. Wand with directing holes for an elliptical steam brewing

Serial interface for external connection **LED lights** on the brewing groups

White filter holders for 1 and 2 cups

Nut wood kit: filter holders and joysticks

Aesthetic customization (colour options on the website gallery)

•

•